

# **Concrete Bid**

05/01/2013

City of Gallatin

## **1.0 Introduction**

The City of Gallatin is accepting bids for **Concrete**. Bids will be due on May 9<sup>th</sup> 2013 at 1:30 pm in a sealed envelope clearly marked: **Concrete Bid**.

## **1.1 Scope of Work**

The City of Gallatin seeks pricing for annual pricing for the purchase of concrete. The City purchase an estimated 1000 + yards per year.

## **2.0 Technical Requirements**

See Concrete Specifications

## **3.0 Vendor Requirement**

Vendor shall deliver f.o.b. to Gallatin, TN.

Vendor must complete attached Price Sheet.

Price good for 1 year, with a possible one year extension.

## **4.0 Evaluation of Proposals**

The City of Gallatin will award the contract to lowest responsible and responsive bidder meeting specifications, quality, and performance standards pursuant to the Municipal Purchasing Act of 1983. Response will be based on the following factors;

- Completeness of response
- Cost
- Vendor track record, including references
- Quality of service
- Quality of product

## **5.0 Contract Award**

The City of Gallatin reserves the right to reject any or all proposals and to waive any informality found therein. The City of Gallatin will award a contract based on evaluations described above.

## **6.0 Proposal Submission**

**BID DUE DATE: May 9<sup>th</sup> 2013 at 1:30 pm**

Proposals shall be directed to the attention of:

Finance Department

Attn: J.R.Smith, Jr

132 West Main Street

Gallatin, TN 37066

Telephone: 615-451-5963

## PRICE SHEET

**Pricing will be all inclusive pricing**

	<4.25 Yards	4.25 - 10 Yards	10 – 50 Yards	>50 Yards
Flowable Fill				
Concrete 3000 psi Small Stone				
Concrete 3000 psi Regular Stone				
Concrete 3500 psi Small Stone				
Concrete 3500 psi Regular Stone				
Concrete 4000 psi Small Stone				
Concrete 4000 psi Regular Stone				
Split Load Fee				

Name of Company: \_\_\_\_\_

Address: \_\_\_\_\_

Telephone: \_\_\_\_\_

Signature: \_\_\_\_\_

Print Name: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_

TECHNICAL SPECIFICATIONS  
FOR  
FLOWABLE FILL MATERIAL (FLOWABLE MORTAR)

2. Materials

Materials used shall meet the following requirements of TDOTSS, 1995.

<u>Material</u>	<u>Subsection</u>
Portland Cement, Type 1	901.01
Fly Ash, Class C or Class F	AASHTO M 295
Water	918.01
Chemical Additives	918.09
Air Entraining Admixtures	918.09

Fine aggregate shall conform to the requirements of TDOTSS, 1995, Subsection 903.01 - Fine Aggregate for Concrete except that the gradation shall be as follows:

<u>Sieve Size</u>	<u>Percent Passing</u>
3/4 inch	100
No. 200	0-10

Proportioning

Flowable mortar shall be proportioned as follows:

<u>Material</u>	<u>Per Cubic Yard</u>
Portland Cement, Type 1	100 lbs.
Fly Ash, Class C or F	250 lbs. (Minimum)
Fine Aggregate	2800 lbs.
Water	60 gal. (Approximate)